

PŘEKLAD

dne: 11-05-2016

ISO VIEW FOR
REFERENCE ONLY
ISO POHLED PRO
LEŽBY NÁKOPNOSTČAROVANOU ČAROU OZNAČENÍ
POKICE POUŽITÍ PŘED
OPRAVOVÁNÍM
(x ROVINY)
PHANTOM LINES DENOTE
POSITION OF SURFACE
BEFORE MACHINING
(2x SURFACES)TRUE VIEW ON TOP FLANGE
POHLED NA HORNÍ PŘÍRUBU11-05-2016
24/16/00574
ARCHIV
O
OCHRANA PŘED KOROZÍ
RUST PROTECTION WN 12 480 - GRADE 3F

| | | | | | |
|--|--|---------------|--------|--|--|
| First angle projection | 01 | State was RFP | 146786 | | |
| General tolerance (GT) in mm | STAV BYL RFP | | | | |
| Size range | Index alteration Change no. Fit Toler. | | | | |
| Inspection dm. | Material: EN 10025 S355J0 | | | | |
| Auxiliary dm. | Weight: in kg 156.0 | | | | |
| GT coarse | Title: Profile | | | | |
| SA 2 1/2 acc. ISO 8501-1 | PROD. Scale 1:5 | | | | |
| without burrs acc. WN 11310 | Sheet: 1 | | | | |
| Permissible top-end rounding during flame cutting (also positive bead acc. WN 10572) | of: 2 | | | | |
| oil-free / free of grease | Drawing number 14014012913 | | | | |
| oiled | Drawing number 14014012913 | | | | |
| paint permissible | Drawing number 14014012913 | | | | |
| alternatively identify condition at time of delivery with an X | Drawing number 14014012913 | | | | |
| en | Drawing number 14014012913 | | | | |

Released

14014012913001

A1