

PŘEKLAD
dne: 17. 12. 2014
PROVEDL/A
TLOUŠŤKA STAT. NENÍ T. RADIUS 4 RADIUS OHYBU



- 2 -03- 2015
ARCHIV
2
N.2 14/01402

NOTA :
- Metal sheet thickness : 6 mm
- Radii without dimension : R = 10
- Bend radii : R = 1

Condition at time of delivery	
de-scaled (degree of purity SA 2 1/2 acc. ISO 8501-1)	X
without burrs acc. WN 11310	
Permissible top-end rounding during flame cutting (also positive bead acc. WN 10572)	
oil-free / free of grease	
oiled	
oiling permissible	X
Indicate the required condition at time of delivery with an X.	

02

LASER cutting tolerances NOTA : min cutting radius without dimensions R = 1 mm unless otherwise specified					
≤ 30	30< ≤ 120	120< ≤ 400	400< ≤ 1000	1000 <	+0,5 -0,5
± 0,5	± 0,8	± 1,0	± 1,5	± 2,0	

First angle projection

General tolerance (GT) in mm

Size range	≤ 30	> 30 ≤ 120	> 120 ≤ 400	> 400 ≤ 1000	> 1000
GT coarse					
L	1	2	2	3	4
∠	1	2	4	6	

Lengths (L) and angle (∠) ± GT

Tolerance Symbols ISO 1101

○ roundness	=1/2a-Tol.
straightness/flatness	= GT
concentricity/run out	= GT
symmetry	= GT
// parallelism	= GT
⌖ position	= GT

Languages: en,fr

Index	alteration	Change no	Fit	Toler.
02	Adding Ø13	T48720		
	Oiled --> oiled permissible			

	Date	Name
Inspection dim.		
Auxiliary dim.		
Drawn	9.12.2013	J.Fanlevy
Checked	10.12.2013	K.Praust
Authd	10.12.2013	K.Peleitor
M.check.	13.1.2014	J.LaCosse

Material: S235JR following EN10025-2
Blank no:
Weight: in kg 3.5
Title: plate rear
PROD.
Scale 1:2
Sheet: 1 of: 1
Drawing number: 11914010502

Confidential document
Refer to protection notice ISO 16016
Repl.
Orig. 11914010502d001
A1

Released