



LM/18/00036

NEKOTOVANÉ POLOHĚY R2
undimensioned radii R2
Bend Radii R6
POLOHĚY OHYBURNĚ

<p>STAV BVL RFQ PRIVAN KOUMLA PRUHEAU</p>		<p>TS4861</p>	
<p>02 State was RFQ</p>		<p>alteration</p>	
<p>Diameter dimension added</p>		<p>Change no</p>	
<p>Fit</p>		<p>Toler:</p>	
<p>First angle projection</p>		<p>Weight: in kg</p>	
<p>General tolerance (GT) in mm</p>		<p>13.6</p>	
<p>Size range</p>		<p>Production Scale</p>	
<p>30 120 400 1000</p>		<p>1.5</p>	
<p>30 120 400 1000</p>		<p>Sheet: 1 of: 1</p>	
<p>Index</p>		<p>Drawing number</p>	
<p>alteration</p>		<p>55044230301</p>	
<p>Inspection dim.</p>		<p>Released</p>	
<p>Auxiliary dim.</p>		<p>107317/1020/001002</p>	
<p>Date</p>		<p>A2</p>	
<p>Name</p>			
<p>Checked</p>			
<p>Auth'd</p>			
<p>Checked</p>			
<p>108.01.2015</p>			
<p>108.01.2015</p>			
<p>S.Boisfeld</p>			
<p>M.Kitup</p>			
<p>UG</p>			
<p>Confidential document</p>			
<p>Refer to protection notice ISO 1676</p>			
<p>Regl.</p>			
<p>Languages:</p>			
<p>DE/EN</p>			
<p>Condition at time of delivery</p>			
<p>de-scaled (degree of purity SA 2 1/2 acc. ISO 8501-1)</p>			
<p>without burrs acc. WN 1930</p>			
<p>Permissible top-end rounding during flame cutting (also positive bead acc. WN 10572)</p>			
<p>oil-free / free of grease</p>			
<p>oiled</p>			
<p>oiling permissible</p>			
<p>Indicate the required condition at time of delivery with an X.</p>			
<p>4</p>		<p>5</p>	
<p>1</p>		<p>6</p>	

СТАВ ДОДАЊИ :
БЕХ ОКУЈИ
БЕХ МАСТНОТ

Condition at time of delivery	
de-scaled (degree of purity SA 2 1/2 acc. ISO 8501-1)	>
without burrs acc. WN 1310	-
Permissible top-end rounding during flame cutting (also positive bead acc. WN 10572)	-
oil-free / free of grease	>
oiled	-
oiling permissible	-
Indicate the required condition at time of delivery with an X.	

Indicate the required condition at time of delivery with an X.