



*Signature*

15-01-2000

undimensioned radii R 10

ARCHIV



Tolerances for section  
to DIN 6930 Part 2  
accuracy grade m

outline length WN 10535

outer ... 2014 ... mm

inner ... 110 ... mm

Condition at time of delivery	
de-scaled (degree of purity SA 2 1/2 acc. ISO 8501-1)	X
without burrs acc. WN 1130	X
Permissible top-end rounding during flame cutting (also positive bead acc. WN 10572)	X
oil-free / free of grease	X
altered	
oil permissible	
alternatively identify condition at time of delivery with an X	

First angle projection	01	1010 → PROD. 9.9 → 19.8, 19.9 → 197.6, 1220 → 208	T04009		
General tolerance (GT) in mm		5.69 kg → 5.56 kg; edited: 106			
Size range					
Index					
Inspection dim.					
Auxiliary dim.					
Date					
Name					
Blank no.					
Material: S235JR					
Weight: in kg					5.56
PROD. Scale					1:2
Sheet: 1 of 1					
Drinking number					3964222301
Confidential document					
Refer to protection notice ISO 10016					
Released					

3964222301\_DRW\_000\_011h288\_dehamap63s\_DE440F\_2007-12-21T10:02:30-01-678897\_KE5\_W244b\_104