



21 -07- 2020
ARCHIV

ZM/20/00351 (B) - PŘENESENÍ INTERNÍHO INDEXU OTVORU 4x Ø 14,8
21.7.2020 Tisovský M.

Condition at time of delivery	
de-scaled (degree of purity SA 2 1/2 acc. ISO 8501-1)	–
without burrs acc. WN 11310	X
Permissible top-end rounding during flame cutting (also positive bead acc. WN 10572)	–
oil-free / free of grease	X
oiled	–
oiling permissible	–
Indicate the required condition at time of delivery with an X.	

First angle projection		02	CO to Prod	T130932	
General tolerance (GT) in mm Size range		Index	alteration	Change no	Fit / Toler.
	30 / 120 / 400 / 1000	PPAP-Level 1 / WN 50020	Material: EN 10025 S355J0		Weight: in kg
	≤ 30 / ≤ 120 / ≤ 400 / ≤ 1000	Inspection dim. Aux.dim. ( )	Blank no:		57.5
GT coarse			Date / Name		
L 1 2 2 3 4		Drawn 17.10.2019 G.Selick	Title: plate Aftertreatment Box Housing		Prod.
◁ 1 2 4 6		Checked 17.10.2019 K.Prosser			Scale 1:5 1:10
Lengths (L) and angle (⊥ ∠) = ±GT		Auth'd 17.10.2019 C.Greenrace			
Tolerance Symbols ISO 1101		M.check. 18.10.2019 L.Hrebel			
○ roundness =1/2a-Tol.					
– ▱ straightness/flatness = GT					
◎ concentricity/run out = GT					
⌯ symmetry = GT					
/ / parallelism = GT					
⊕ position = GT					
Languages: EN		Confidential document Refer to protection notice ISO 16016	Drawing number / / 14015811955		Sheet: 1 of: 2
			Repl.	Orig.	

Released

3427266/D2D/001/02 A1

14015811955V02EN4001