



PŘEKLAD

dne: 12-05-2016

PROVEDL/A
JANA PROKEŠOVÁ

1:5



Pictorial View

2M/16/00518

13-05-2016

ARCHIV

1

ILUSTROVÁNÝ
POHLED

STAV DODÁNÍ:
ODVÁPNUTÝ
BEZ OTŘEPŮ
ODMÁŠTĚNÝ

Condition at time of delivery	
de-scaled (degree of purity SA 2 1/2 acc. ISO 8501-1)	x
without burrs acc. WN 11310	x
Permissible top-end rounding during flame cutting (also positive bead acc. WN 10572)	---
oil-free / free of grease	x
oiled	---
oiling permissible	---
Indicate the required condition at time of delivery with an X.	

First angle projection	03	Length 42.7 was 22.7	T77605		
General tolerance (GT) in mm		DEKLA 42,7 BYLA 22,7			
Size range					
≤ 30	≤ 120	≤ 400	≤ 1000		
GT coarse					
L	1	2	3	4	
≤ 30	≤ 120	≤ 400	≤ 1000		
Lengths (L) and angle (L/Δ) = ± GT					
Tolerance Symbols ISO 1101					
○ roundness = 1/2a-Tol.					
□ straightness/flatness = GT					
◎ concentricity/run out = GT					
≡ symmetry = GT					
// parallelism = GT					
⊕ position = GT					
Languages: EN					
Confidential document					
Refer to protection notice ISO 16016					
Material: CR4 GP					
Blank no:					
Title: pipe					
Weight: in kg 0.2					
Prod. Scale 1:1					
1:5					
Sheet: 1 of 1					
Drawing number 14015712702					
Repl.					
Orig.					

Approved

1295878/D2D/001/03

A3

14015712702V03EN001