


PŘEKLAD

dne: 12-05-2016

PROVEDL/A  
JANA PROKEŠOVÁ



Pictorial View

1:5

ILUSTROVANÝ  
POHLED

13-05-2016

ARCHIV



2M/16/00518

STAV DODÁNÍ:  
DODÁNÍ  
BEZ OTŘEPŮ  
DOMYŠLENÝ

Condition at time of delivery	
de-scaled (degree of purity SA 2 1/2 acc. ISO 8501-1)	x
without burrs acc. WN 11310	x
Permissible top-end rounding during flame cutting (also positive bead acc. WN 10572)	...
oil-free / free of grease	x
oiled	...
oiling permissible	...
Indicate the required condition at time of delivery with an X.	

First angle projection	02	State was RFQ	STAV BYL RFQ	T48032		
General tolerance (GT) in mm	Index alteration Change no Fit Toler.					
Size range	Inspection dim. Auxiliary dim. ( )					
GT coarse	Material: CR4 GP					
L 1 2 2 3 4	Blank no:					
1 2 4 6	Title:					
Lengths (L) and angle (L/∠) = ± GT	Drawing number					
Tolerance Symbols ISO 1101	14015712701					
○ roundness = 1/2a-Tol.	Weight: in kg					
□ straightness/flatness = GT	0.5					
⊙ concentricity/run out = GT	PROD.					
≡ symmetry = GT	Scale					
/ / parallelism = GT	1:1					
⊕ position = GT	1:5					
Languages: en	Sheet: 1 of 1					
Confidential document	Repl. Orig.					
Refer to protection notice ISO 16016	Released					

14015712701d001

A3