

PŘEKLAD
dne: 15. 04. 2013
PROVEDLA

- 9 -07- 2013
ARCHIV

3

NZ 13/00347

Rz40

-0.01 -1.2 +1.2 +0.1 -0.1 -0.1 -0.2 -0.3

PLATE 2 HOTOVÝ 2 KS 130x40

plate manufactured out of a flat bar 130x40

Condition at time of delivery	
de-scaled (degree of purity SA 2 1/2 acc. ISO 8501-1)	X
without burrs acc. WN 1330	
Permissible lap-end rounding during flame cutting (also positive bead acc. WN 10572)	–
oil-free / free of grease	X
oiled	–
oiling permissible	–
Indicate the required condition at time of delivery with an X.	

First angle projection

General tolerance (GT) in mm

Size range	≤ 30	> 30 ≤ 120	> 120 ≤ 400	> 400 ≤ 1000
GT coarse				
L	1	2	3	4
m	1	2	4	6

Lengths (L) and angle (∠): ±GT

Tolerance Symbols ISO 1101

○	roundness	=1/2a-Tol.
⏥	straightness/flatness	= GT
⌖	concentricity/run out	= GT
⌯	symmetry	= GT
//	parallelism	= GT
⌖	position	= GT

Languages: deen

Index	alteration	Change no	Fit	Toler.
04	dimensioning added	150304		

Inspection dim.		Material: S355J2+N	Weight: in kg 36.3
Auxiliary dim.		Blank no:	
	Date	Name	
Drawn	7.3.2013	D.Schielmann	Title: plate outer mast - reach carriage right
Checked	21.3.2013	S.Geißler	
Auth'd	21.3.2013	J.Neumann	PROD.
M.check.	25.3.2013	K.Stein	Scale: 1.2 1:1
Drawing number	/ / 150144615O6		Sheet: 1 of: 1
Repl. 150144613O7		Orig.	
150144615O6d001			A1

Released