



PŘEKLAD
dne: 17. 12. 201
PROVEDLA
Vitová

- 4 -03- 2015
ARCHIV
1

NZ 14/01402

TLOUŠŤKA MAT.
NEBOŤ. RADIUSY
RADIUS OHYBU

(01)

NOTE :
- Metal sheet thickness : 20 mm
- Radii without dimension : R = 10
- Inside bend radii R = /

(01)

Condition at time of delivery	
de-scaled (degree of purity SA 2 1/2 acc. ISO 8501-1)	X
without burrs acc. WN 11310	
Permissible top-end rounding during flame cutting (also positive bead acc. WN 10572)	
oil-free / free of grease	
oiled	
oiling permissible	X
Indicate the required condition at time of delivery with an X.	

LASER cutting tolerances
NB: in the cutting radius without dimensions R = 1 mm unless otherwise specified

≤ 30	30< ≤ 120	120< ≤ 4.00	4.00< ≤ 1000	1000 <
± 0,5	± 0,8	± 1,0	± 1,5	± 2,0

+0.5 −0.5

First angle projection

General tolerance (GT) in mm

Size range	≥ 30 ≤ 120	≥ 120 ≤ 4.00	≥ 4.00 ≤ 1000	≥ 1000
GT coarse				
L	1	2	2	3	4
≈	1	2	4	6

Lengths (L) and angle (∠) ± GT

Tolerance Symbols ISO 1101
- roundness = 1/2a-Tol.
- straightness/flatness = GT
- concentricity/run out = GT
- symmetry = GT
- parallelism = GT
- position = GT

Languages: en,fr

Index	alteration	Change no	Fit	Toler.
01	Adding note	T48720		
	Oiled --> Oiled permissible			

Inspection dim.
Auxiliary dim. ( )

	Date	Name
Drawn	10.12.2013	J.Fantera
Checked	13.12.2013	P.Proust
Authd	20.12.2013	R.Peleter
M.check.	13.1.2014	J.LeCosne

Material: S235JR following EN10025-2
Blank no:
Title: reinforcement top
Drawing number: 11914.012802
Weight: in Kg 8.4
PROD.
Scale 1:1
Sheet: 1 of: 1

Confidential document
Refer to protection notice ISO 16016
Repl.
Orig. 11914.012802d001
A1

Released