



PROVEDL/A

2 -03- 2015
ARCHIV

2

✓ N2 14/01402

N2 14/07402

<p>Condition at time of delivery</p> <p>de-sticked degree of purity ≥ 12 or ≥ 50 <input checked="" type="checkbox"/> X</p> <p>without burrs etc. WH 1930</p> <p>Permissible top-and rounding during flame cutting takes positive bend etc. WH 19272</p> <p>at-free f free of grease</p> <p>along permissible</p> <p>Indicate the required condition at time of delivery with an X.</p>	<p>Number</p> <p>First angle projection</p> <p>General tolerance (GT) in mm</p> <p>Size range</p> <p>≥ 30 to < 100 ≥ 100 to < 400 ≥ 400 to < 1000</p> <p>GT coarse</p> <p>LT 1 2 3 4</p> <p>LT 1 2 3 4</p> <p>Lengths L1 and angle L2 ≥ 10</p> <p>Tolerance Symbols ISO 101</p> <p>o roughness</p> <p>GT roughness/finish: a GT</p> <p>o concentricity cyl: a GT</p> <p>o symmetry</p> <p>o parallelism</p> <p>o position</p> <p>tolerances</p> <p>envr</p>	<p>Material <input checked="" type="checkbox"/> Steel permissible (see 518 \rightarrow 819 (see 518 \rightarrow 9))</p> <p>Inspection dim. alteration</p> <p>Drawn by: <input type="text"/></p> <p>Date Name</p> <p>Checked: R.1204 R.1204 R.1204 R.1204</p> <p>Material: 525RS following ENISO-2</p> <p>Blank no.</p> <p>Title:</p> <p>support</p> <p>call left</p> <p>PROD. Scale 1:1</p> <p>Sheet 1 of 1</p> <p>1914.010909</p> <p>Released</p> <p>1914.095940001</p> <p>Drp.</p>
--	---	--