

Gestreckte Länge
streched length

1003,0mm
+ 157,1mm
+ 828,0mm
+ 139,6mm
+ 127,2mm

= 2254,9mm







(1:10)



Geländer wahlweise als Biege-Schweißteil
oder reines Biegeteil gefertigt!
handrail optional manufactured as
bendpart or weldpart!

2410885 = spigelbildlich
2410885 = mirror-inverted

Achtung:
Alle Schweißnähte müssen sauber
verschliffen sein, ohne Ansätze!
PLEASE NOTE:
ALL WELDED SEAMS MUST BE
GRINDED NEATLY, NO EDGES!

B100 = Ohne Beschichtung / KWN 2186915

REFER TO PROTECTION NOTICE ISO 16016		MATERIAL				TYPE	DOCUMENT-NO.	VERS. STATUS
		ECN-NO. 46818		MAT-SPEC.		UGD	4754254	01 SF
HSTG			DRAWING BY	APPROVED BY	LAST MODIFIED BY	WEIGHT 4,45 KG	SCALE	FORMAT A2
ISO 8015	ISO 14405	DATE	08.08.2014	13.09.2016	14.07.2016	FIRST USE K018		SHEET OF 1 / 1
ISO 2768	m/K	NAME	EXBERNHARDJ	KLGEYWITZT	EXBERNHARDJ			
ISO 13920	BF	DESCRIPTION						
ISO 8062	CT10	Geländerrohr FR re MR110 EVO2						
ISO 9013	231	Hand rail tube FR right MR110 EVO2						
ISO 1101	EN ISO 1302							
beliebig at liberty	R_z = 25					PART NO. 2410893		REV.NO. 01
R_z = 100	R_z = 6,3							
KWN 2188113								

- Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Geschmacksmustereintragung vorbehalten - The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design -