

ⓐ ZM/18/00915-OTVOR 63,5+-0,2-2x PŘEDPÁLEN NA 62 MM.
1.8.2018

ⓑ - ZM/20/00204-OTVOR 63,5+-0,2-2x PŘEDPÁLEN NA 61 MM.
16.4.2020 H

PŘEKLAD
dne: 17-04-2015
PROVEDL/A

20-04-2020
ARCHIV
3

-0.4
-0.2

NEUVOLŇOVANÝ
DETAIL DLE 3D DAT

Non-dimensioned details according to 3D-Data

Autogenous flame cutting WN 10 572				
Thickness of the cut	≤ 20	> 20 ≤ 40	> 40 ≤ 60	> 60 ≤ 100
Rectangularity Inclination	1,0	1,4	1,8	2,2
Surface roughn. R_z	100	160	160	250
all possible cuttingtool entries marked by:				

Tolerances for section to DIN 6930 Part 2 accuracy grade g

outline length WN 10535		
outer	3469.2	mm
inner	1137.5	mm

Condition at time of delivery	
de-sccled (degree of purity SA 2 1/2 acc. ISO 8501-1)	X
without burrs acc. WN 11310	X
Permissible top-end rounding during flame cutting (also positive bead acc. WN 10572)	–
oil-free / free of grease	X
oiled	–
oiling permissible	–

Indicate the required condition at time of delivery with an X.

First angle projection

General tolerance (GT) in mm

Size range	> 30 ≤ 120	> 120 ≤ 4.00	> 4.00 ≤ 1000
GT coarse			
L 1	2	2	3 4
⊿ 1	2	4	6

Lengths (L) and angle (L, ⊿) = ± GT

Tolerance Symbols ISO 1101

○	roundness	=1/2a-Tol.
– ▱	straightness/flatness	= GT
◎ ↗	concentricity/run out	= GT
⌯	symmetry	= GT
//	parallelism	= GT
⌖	position	= GT

Languages: EN

Confidential document
Refer to protection notice ISO 16016

Index	alteration	Change no	Fit	Toler.
02	hole 44+3 was 44+1	T6935 3		
	Inspection dim. ⬭			
	Auxiliary dim. ( )			

	Date	Name
Drawn	24.03.2015	A.Schäflein
Checked	24.03.2015	M.Pieritz
Authd	24.03.2015	B.Cajan
M.check.	08.04.2015	C.Ullrich

Material: S355J2+N
Blank no:
Weight: in kg 29.6
Title: plate LH R25
Prod.
Scale 1:2
Sheet: 1 of: 1
Drawing number / / 11204012570
Repl. 11204012521 Orig.
Released
6 3012653/02D/001/02 A2
11204012570V02EN0001