



02A-ZM17/00134-SKUTEČNÝ TVAR DÍLCE (VÝPALKU)
ZKRESLEN NA LISTU Č.2

7.2.2017 HRUBÝ

PŘEKŁAD

PROVEDĚNIA

10-12-2017

ARCHIV

10-12-2017

ARCHIV

10-12-2017

ARCHIV

10-12-2017

ARCHIV

10-12-2017

ARCHIV

10-12-2017

ARCHIV

10-12-2017

ARCHIV

10-12-2017

ARCHIV

10-12-2017

ARCHIV

10-12-2017

ARCHIV

NOTA :
- Metal sheet thickness : 6 mm
- Radii without dimension : R = 2
- Bend radii : R = 1
- Unfolded length (for info) = 1

Condition at time of delivery	SA 2 1/2 acc. ISO 5501-1	X
Permissible top-end rounding during flame cutting (also positive bend acc. DIN 15772)	ok-free / free of grease	X
Indicate the required condition at time of delivery with an X.		
LASER cutting tolerances	MDA : min. cutting tolerances without dimensions R ± 1 mm unless otherwise specified ± 0.5 ± 0.8 ± 1.0 ± 1.5 ± 2.0	
Condition at time of delivery	SA 2 1/2 acc. ISO 5501-1	X
Permissible top-end rounding during flame cutting (also positive bend acc. DIN 15772)	ok-free / free of grease	X
Indicate the required condition at time of delivery with an X.		
LASER cutting tolerances	MDA : min. cutting tolerances without dimensions R ± 1 mm unless otherwise specified ± 0.5 ± 0.8 ± 1.0 ± 1.5 ± 2.0	

Released 6 11914.00520001