

PŘEKLAD
13.12.2019
PROVEDLA
BRANDOVÁ EVA

rozvin
flat pattern
1:2

linie ohybu
bend line

2x R10

1:10
Pictorial View
znázornění

ARCHIV
13.12.2019
1
ZM/19/00778

Condition at time of delivery

de-scaled (degree of purity
SA 2 1/2 acc. ISO 8501-1)
without burrs acc. WN 1130

Permissible top-end rounding
during flame cutting (also
positive bead acc. WN 10572)

oil-free / free of grease
oiled

oiling permissible

Indicate the required condition
at time of delivery with an X.

outline length WN 10535

outer 2074 mm
inner -- mm

Tolerances for section
to DIN 6930 Part 2
accuracy grade m

First angle projection	02	CO to Prod	T135533
General tolerance (GT) in mm Size range	PPAP-Level 1 / WN 50020		
≤ 30	30-120	120-400	400-1000
≤ 30	30-120	120-400	400-1000
Index	alteration		
Material: EN 10025 S275 JR	Weight: in kg 9.67		
Blank no:	Title:		
plate	fuel tank T5		
Prod. Scale 1:2	Sheet: 1 of 1		
Drawing number 14015711424	Confidential document		
Refer to protection notice ISO 16018	Repl.		
EN	3426932/D2D/001/02 A2		