



- 6 -02- 2018

ARCHIV

1

LM/18/00036

NEKÓTOVANÉ POLOHĚRY MAX R1
undimensioned radii max. R 1

02

DIN 50979 - ZnFe12/Fn/IT2

First angle projection	02	change the coatings to Cr(VI)-free coatings	T92692														
		ZMĚNA POVRCHOVÉ ÚPRAVY															
General tolerance (GT) in mm	Index	alteration	Change no	Fit	Toler.												
Size range																	
<table border="1"> <tr> <td>≤ 30</td> <td>> 30 ≤ 120</td> <td>> 120 ≤ 400</td> <td>> 400 ≤ 1000</td> </tr> <tr> <td>1</td> <td>2</td> <td>3</td> <td>4</td> </tr> </table>	≤ 30	> 30 ≤ 120	> 120 ≤ 400	> 400 ≤ 1000	1	2	3	4	PPAP -	Material: S235JR	Weight: in kg						
≤ 30	> 30 ≤ 120	> 120 ≤ 400	> 400 ≤ 1000														
1	2	3	4														
GT fine	Inspection dim. <input type="radio"/> Aux.dim. ()	Blank no:	0.039														
<table border="1"> <tr> <td>L</td> <td>0,2</td> <td>0,5</td> <td>0,8</td> <td>2</td> <td>4</td> </tr> <tr> <td>≤ 30</td> <td>0,1</td> <td>0,2</td> <td>0,4</td> <td>1</td> <td>2</td> </tr> </table>	L	0,2	0,5	0,8	2	4	≤ 30	0,1	0,2	0,4	1	2	Date	Name	Title:	Prod.	
L	0,2	0,5	0,8	2	4												
≤ 30	0,1	0,2	0,4	1	2												
Lengths (L) and angle (∠) = ±GT	Drawn	07.04.2017	joining plate	Scale													
Tolerance Symbols ISO 1101	Checked	23.06.2017		1:1													
<ul style="list-style-type: none"> ○ roundness = 1/2ø-Tol. -□ straightness/flatness = AT ⊙ concentricity/run out = AT ≡ symmetry = AT // parallelism = AT ⊕ position = AT 	Auth'd	20.07.2017		Sheet: 1													
	M.check.	24.07.2017		of: 1													
Languages: DE;EN	Confidential document	Repl.	Orig.	55044231701													
	Refer to protection notice ISO 16016																

Released

1194633/D2D/001/02

A4

55044231701V02EN001 55044231701_DRW_000_020631f e1sap304 DE7CA7 2017-12-12T08:47:59 1.000